General Description

The AGMH056N08HM1 combines advanced trench MOSFET technology with a low resistance package to provide extremely low $R_{DS(ON)}$.

This device is ideal for load switch and battery protection applications.

Features

- Advance high cell density Trench technology
- Low $R_{DS(ON)}$ to minimize conductive loss
- Low Gate Charge for fast switching
- Low Thermal resistance
- 100% Avalanche tested
- 100% DVDS tested


Application

- MB/VGA Vcore
- SMPS 2nd Synchronous Rectifier
- POL application
- BLDC Motor driver


Product Summary

BVDSS	RDSON	ID
85V	4.8mΩ	142A


TO-263 Pin Configuration



Top View



Bottom View



Package Marking and Ordering Information

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
AGMH056N08H	AGMH056N08HM1	TO-263	330mm	25mm	800

Table 1. Absolute Maximum Ratings (TA=25℃)

Symbol	Parameter	Value	Unit
VDS	Drain-Source Voltage (VGS=0V)	85	V
VGS	Gate-Source Voltage (VDS=0V)	±20	V
ID	Drain Current-Continuous(Tc=25℃) **(Note 1)**	142	A
	Drain Current-Continuous(Tc=100℃)	101	A
IDM (pluse)	Drain Current-Pulsed **(Note 2)**	568	A
PD	Maximum Power Dissipation(Tc=25℃)	288	w
	Maximum Power Dissipation(Tc=100℃)	144	w
EAS	Avalanche energy **(Note 3)**	380	mJ
TJ,TSTG	Operating Junction and Storage Temperature Range	-55 To 175	℃

Table 2. Thermal Characteristic

Symbol	Parameter	Typ	Max	Unit
RθJA	Thermal Resistance Junction-ambient (Steady State)[1]	---	50	℃/W
RθJC	Thermal Resistance Junction-Case[1]	---	0.52	℃/W

Table 3. Electrical Characteristics (TJ=25℃unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
On/Off States						
BVDSS	Drain-Source Breakdown Voltage	VGS=0V ID=250μA	85	--	--	V
IDSS	Zero Gate Voltage Drain Current	VDS=85V,VGS=0V	--	--	1	μA
IGSS	Gate-Body Leakage Current	VGS=±20V,VDS=0V	--	--	±100	nA
VGS(th)	Gate Threshold Voltage	VDS=VGS,ID=250μA	2.5	2.9	4.0	V
gFS	Forward Transconductance	VDS=5V,ID=20A	--	19	--	S
RDS(on)	Drain-Source On-State Resistance	VGS=10V, ID=20A	--	4.8	6.5	mΩ
Dynamic Characteristics						
Ciss	Input Capacitance	VDS=40V,VGS=0V, F=1MHZ	--	1896	--	pF
Coss	Output Capacitance		--	776	--	pF
Crss	Reverse Transfer Capacitance		--	15	--	pF
Rg	Gate resistance	VGS=0V, VDS=0V,f=1.0MHz	--	1.1	--	Ω
Switching Times						
td(on)	Turn-on Delay Time	VGS=10V,VDS=40V, ID=40A,RGEN=3Ω	--	15	--	nS
tr	Turn-on Rise Time		--	52	--	nS
td(off)	Turn-Off Delay Time		--	38	--	nS
tf	Turn-Off Fall Time		--	24	--	nS
Qg	Total Gate Charge	VGS=10V, VDS=40V, ID=40A	--	57	--	nC
Qgs	Gate-Source Charge		--	19	--	nC
Qgd	Gate-Drain Charge		--	14	--	nC
Source-Drain Diode Characteristics						
ISD	Source-Drain Current(Body Diode)		--	--	142	A
VSD	Forward on Voltage	VGS=0V,IS=20A	--	--	1.2	V
trr	Reverse Recovery Time	IF=20A , dI/dt=100A/μs ,TJ=25℃	--	52	--	ns
Qrr	Reverse Recovery Charge		--	65	--	nc

Notes 1.The maximum current rating is package limited.

Notes 2.Repetitive Rating: Pulse width limited by maximum junction temperature

Notes 3.EAS condition: TJ=25℃,VDD=40V,Vgs=10V,ID=39A, L=0.5mH,RG=25ohm

Typical Characteristics




Fig1. Typical Output Characteristics




Fig2. Typical $V_{GS(TH)}$ Gate -Source Voltage Vs. Tj




Fig3. Typical Transfer Characteristics




Fig4. Typical Normalized On-Resistance Vs. Tj




Fig5. Typical On Resistance Vs Gate -Source Voltage




Fig6. Typical On Resistance Vs Drain Current

Typical Characteristics




Fig7. Typical Source-Drain Diode Forward Voltage




Fig8. Maximum Safe Operating Area




Fig9. Typical Capacitance Vs. Drain-Source Voltage




Fig10. Typical Gate Charge Vs. Gate-Source Voltage




Fig11. Power Dissipation Vs. Case Temperature




Fig12. Maximum Drain Current Vs. Case Temperature

Typical Characteristics




Fig13 . Normalized Maximum Transient Thermal Impedance




Fig14. Unclamped Inductive Test Circuit and waveforms








Fig15. Switching Time Test Circuit and waveforms

●Dimensions（TO-263）












SYMBOL	MILLIMETER		
	MIN	Typ.	MAX
A	4.370	4.570	4.770
A1	0.000		0.250
A2	1.220	1.270	1.420
A3	2.490	2.690	2.890
b	0.700	0.810	0.960
b1	1.170	1.270	1.470
c	0.300	0.380	0.530
D	9.860	10.160	10.360
D1	8.400 REF		
D2	7.073 REF		
E	8.500	8.700	8.900
E1	1.070	1.270	1.470
e	2.540 TYP		
L	14.700	15.100	15.500
L1	1.400	1.550	1.700
L2	2.000	2.300	2.600
θ	0°		9°
θ1	7° TYP		
θ2	7° TYP		
θ3	3° TYP		





Dim.	Min.	Max.
A	9.8	10.2
B	6.1	6.7
C	1.1	1.4
D	0.5	1.0
E	4.6	5.0
F	1.4	1.6
G	0.7	0.9
H	1.17	1.37
I	Typ2.54	
J	9	9.2
K	4.3	4.7
L	1.25	1.35
M	0.02	0.23
N	2.2	2.8
O	0.45	0.55
All Dimensions in millimeter		

TO-263
Marking Instructions:



Disclaimer:

The information provided in this document is believed to be accurate and reliable. However,Shenzhen Core Control Source Electronics Technology Co., Ltd. does not assume any responsibility for the following consequences.Do not consider the use of such information or use beyond its scope.

The information mentioned in this document may be changed at any time without notice.

The products and information provided in this document do not infringe patents. Shenzhen Core Control Source Electronics Technology Co., Ltd. assumes no responsibility for any infringement of any other rights of third parties.The result of using such products and information.

This document is the third version issued on April 10th, 2024. This document replaces all previously provided information.

AGMSEMi It is a registered trademark of Shenzhen Core Control Source Electronics Technology Co., Ltd.

Copyright © 2017 Shenzhen Core Control Source Electronics Technology Co., Ltd. all rights reserved.